

HIGHTOWER PRODUCTS, LC

T E C H N I C A L D A T A S H E E T

HT Mold Sealer

PRODUCT DESCRIPTION

HT mold sealer is a solvent based curable resin that seals the tool and provides a hard, uniform surface for other mold release agents. HT Mold Sealer will also provide a barrier to prevent corrosion on steel tools while they are in storage. However, HT Mold Sealer is not designed to provide corrosion protection for tooling that would be stored outside.

FEATURES AND BENEFITS

- Stable solution. Requires no mixing
- Designed for steel tooling used in rotational molding as well as rubber molding.
- Wets well on room temperature tooling
- Stable up to 600F
- Provides a uniform, continuous film on all steel tooling
- Mild solvent odor

TYPICAL PRODUCT SPECIFICATIONS

Appearance	Clear colorless liquid
Viscosity.....	solvent thin
Specific Gravity.....	0.77
Weight per gallon (lbs.).....	6.4
Flash point.....	105 F

SAFETY-DISPOSAL

Emergency and First Aid Procedures:

Warning. Combustible. contains petroleum distillates.

Eye Contact - If contact with eyes occurs, flush with clean water for 15 minutes and seek medical attention.

Skin Contact - In case of contact, remove contaminated clothing and wash the skin thoroughly with mild soap and water. If irritation develops, seek medical attention.

Ingestion - If ingested, seek medical attention immediately.

Further information regarding health and safety is available upon request.

HT Mold Sealer should be stored indoors. Dispose of in accordance with local authorities.